

TRANSIT CONCRETE MIXER **DRUM WASHOUT SYSTEM**

Patent Application
of

Robert Gjestvang
2590 West 80th Avenue
Denver, Colorado 80221

Attorney

Emery L. Tracy
Reg. No. 34,081
P.O. Box 1518
Boulder, Colorado 80306-1518
Telephone: 303-443-1143
Facsimile: 303-443-1415

Docket No.: G006.PAT-1

TRANSIT CONCRETE MIXER DRUM WASHOUT SYSTEM

The present application is a continuation of pending provisional patent application Serial No. 60/236,217, filed on September 28, 2000, entitled "Transit Concrete Mixer Drum Washout System".

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to a washout system for a transit concrete mixer drum and, more particularly, it relates to a washout system for a transit concrete mixer which is extendible into the mixer drum for delivering pressurized water into the interior of the mixer drum.

2. Description of the Prior Art

Transit concrete mixer drums typically consist of a large mixer drum with internal fins arranged in a corkscrew pattern. The mixer drum is mounted horizontally and rotated about a center axis. As the mixer drum turns, the fins force the concrete into or out of the drum depending on the direction of rotation.

Unfortunately, current concrete mixer drum design does not allow complete removal of the concrete. In fact, when the mixer drum is loaded with fresh concrete and then unloaded, a small amount of concrete remains inside the mixer drum adjacent the fins. In an attempt to remove the remaining concrete, the concrete truck driver or operator will then fill the mixer drum with water in an attempt to wash the remaining concrete from the mixer drum. However, since concrete trucks only carry a maximum of one hundred and twenty-five (125) gallons of water which must be used to water down the load before concrete unloading, the remaining amount of water is not sufficient to clean the mixer drum, especially on the side of the fins facing toward the front of the concrete truck.

Another alternative to remove the concrete prior to hardening within the mixer drum is to load a large amount of water into the mixer drum upon the concrete truck

1 returning to the operation site. Unfortunately, the water travels directly to the front of the
2 mixer drum and does not wash the back side of the fins. The operator typically can not
3 reach far enough into the mixer drum to reach the back side of the fins.

4 The concrete remaining in the mixer drum which is not washed out, the concrete
5 will harden inside the mixer drum. Over time, layers of concrete build up until large
6 amounts of dried, hardened concrete is present inside the mixer drum; reducing the mixer
7 drum volume and mixing with the fresh concrete. The hardened concrete must now be
8 removed by mechanical or chemical means. Neither of the mechanical means nor
9 chemical means are an attractive method for the concrete truck operator due to high costs
10 and environmental hazards. For instance, mechanical means typically requires a person
11 to physically enter the drum with a jackhammer to physically remove the hardened
12 concrete. Chemical means, on the other hand, typically requires dangerous chemical
13 which can contaminate the environment or require special handling and safety
14 procedures.

15 Accordingly, there exists a need for a transit concrete mixer drum washout system
16 which effectively removes concrete from the inside of a mixer drum prior to the concrete
17 hardening therein. Additionally, a need exists for a transit concrete mixer drum washout
18 system which does not require either expensive mechanical removal of hardened concrete
19 or dangerous chemicals harmful to the environment. Furthermore, there exists a need for
20 a transit concrete mixer drum washout system which is extendible into the mixer drum to
21 inject pressurized water to all areas thereby removing the concrete therein prior to
22 hardening.

23 24 SUMMARY

25 The present invention is a washout system for cleaning concrete and other
26 materials from the inside surface of a concrete mixer drum with a fluid. The concrete
27 mixer drum mounted to a concrete truck or the like with the fluid stored in a
28 predetermined fluid source with the fluid source activatable to release fluid. The washout
29 system comprises a telescoping pipe assembly extendible into the mixer drum with the

1 telescoping pipe assembly having a first end and a second end and the first end fluidly
2 connected to the fluid source. A spray bar is fluidly connected to the second end of the
3 telescoping pipe assembly and a plurality of nozzles positioned circumferentially about
4 and longitudinally along the spray bar wherein upon activation of the fluid source, thereby
5 introducing fluid into the telescoping pipe assembly, the second end of the telescoping
6 pipe assembly extends into the mixer drum.

7 The present invention additionally includes a method for cleaning concrete and
8 other materials from the inside surface of a concrete mixer drum with a fluid. The
9 method comprise providing a telescoping pipe assembly, providing a spray bar, forming a
10 plurality of nozzles along the spray bar, connecting the spray bar to the telescoping pipe
11 assembly, introducing fluid into the telescoping pipe assembly, and extending at least a
12 portion of the telescoping pipe assembly into the mixer drum.

13 The present invention further includes an assembly for cleaning concrete and
14 other materials from the inside surface of a concrete mixer drum with a fluid. The
15 assembly comprises telescoping means extendible into the mixer drum and spray means
16 connected to the telescoping means.

18 BRIEF DESCRIPTION OF THE DRAWINGS

19 FIG. 1 is a sectional side view illustrating a transit concrete mixer drum washout
20 system, constructed in accordance with the present invention, with the washout system
21 extended into the mixer drum;

22 FIG. 2 is an elevational side view illustrating the transit concrete mixer drum
23 washout system, constructed in accordance with the present invention, with the washout
24 system in the starting position; and

25 FIG. 3 is an elevation side view illustrating the transit concrete mixer drum
26 washout system, constructed in accordance with the present invention, with the washout
27 system in the activated position.

29 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

1 As illustrated in FIGS. 1 – 3, the present invention is a washout system, indicated
2 generally at 10, for washing concrete or the like from a transit concrete mixer drum 12 or
3 other type of vehicle with difficult accessibility. As discussed above, transit concrete
4 mixer drums 12 typically consist of a large mixer drum 12 with internal mixing fins 14
5 arranged in a substantial corkscrew pattern. The mixer drum 12 is typically mounted
6 substantially horizontally upon a concrete truck and rotated about a center axis.
7 Depending on the desired direction of rotation, as the mixer drum 12 rotates about the
8 center axis, the mixing fins 14 actually force the concrete deeper into the mixer drum 12
9 to insure complete mixing of the concrete or out of the mixer drum 12 for deposit of the
10 concrete in a desired location.

11 The washout system 10 of the present invention includes a telescoping pipe 16
12 having a plurality of pipe sections with each pipe section being receivable within the
13 adjacent pipe section such that in the starting position, the washout system 10 is
14 completely retracted. At the end of the telescoping pipe 16, a spray bar 18 is fluidly
15 connected thereto. The spray bar 18 preferably has a plurality of nozzles 20 positioned
16 circumferentially about and longitudinally along the spray bar 18 to direct water in all or
17 substantially all directions within the mixer drum 12, including to hard-to-reach areas
18 behind the mixing fins 14 where concrete tends to collect thereby insuring complete
19 washout of the mixer drum 12.

20 The telescoping pipe 16 is connected to a water supply 22 and is extendible
21 completely into the mixer drum 12 to reach the back side of all of the mixing fins 14.
22 When pressurized water is applied to the telescoping pipe 16, the washout system 10 of
23 the present invention is activated with the spray bar 18 automatically or manually
24 extending completely into the mixer drum 12. The nozzles 20 of the spray bar 18 direct
25 the pressurized water onto the inside surfaces of the mixer drum 12, including the back
26 side of the mixing fins 14, not normally reachable through any other conventional mixer
27 drum washing method.

28 The washout system 10 is connectable to a water supply 22, either from a
29 standpipe at the operation site or the water supply stored on the concrete truck, if any

1 remains after removal of the concrete at the desired location. Furthermore, non-toxic,
2 environmentally friendly cleaning agents can be used, although not necessarily required,
3 to assist in thoroughly cleaning the inside surfaces of the mixer drum 12, including the
4 mixing fins 14.

5 As described above, preferably, the length of the telescoping pipe 16 is sufficient
6 to reach the front of the farthest forward mixing fin 14 of the mixer drum 12 and wash the
7 back side of all of the mixing fins 14 to inhibit any concrete building up on the back side
8 of the fins 14 or elsewhere within the mixer drum 12. The nozzles 20 are preferably
9 recessed relative to the spray bar 18 to inhibit any potential problems associated with
10 retracting the spray bar 18 into the telescoping pipe 16 once the mixer drum 12 washout is
11 complete and deactivated. Furthermore, the angle of the telescoping pipe 16 relative to
12 the ground should be equivalent to the interior layout of the mixer drum 12 so that the
13 telescoping pipe 16 does not become caught or broken off inside the mixer drum 12.

14 The spray bar 18 of the washout system 10 of the present invention is preferably
15 includes an automatic return system 24 such as a weight and pulley or spring. The return
16 system 24 allows the spray bar 18 to automatically retract into the telescoping pipe 16
17 once the water pressure to the telescoping pipe 16 is turned off or otherwise disconnected.
18 The automatic return system 24 allows the spray bar 18 and the telescoping pipe 16 to
19 return to the starting, stored position and not remain inside the mixer drum 12 when the
20 concrete truck is in transit. It should be noted, however, that a manual return system 24 is
21 also within the scope of the present invention.

22 It should be noted that the washout system 10 can be connected directly to the
23 concrete truck or the standpipe. Therefore, the washout system 10 can be transported to a
24 job location for immediate clean out.

25 The foregoing exemplary descriptions and the illustrative preferred embodiments
26 of the present invention have been explained in the drawings and described in detail, with
27 varying modifications and alternative embodiments being taught. While the invention
28 has been so shown, described and illustrated, it should be understood by those skilled in
29 the art that equivalent changes in form and detail may be made therein without departing

1 from the true spirit and scope of the invention, and that the scope of the present invention
2 is to be limited only to the claims except as precluded by the prior art. Moreover, the
3 invention as disclosed herein, may be suitably practiced in the absence of the specific
4 elements which are disclosed herein.

5

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000